# Offer

**Ref.:** **NEW ORDER - REV1** **Installation :ITEM 2** **Offer N° :** **FT** **of**

| INSTALLATION | GIVEN | SUPPOSED |
|---|---|---|
| Type of roping | 1 : 1 | |
| Car speed [m/s] | | 1,06 |
| Duty load [Kg] | | |
| Car weight [Kg] | | |
| Ropes n° x diameter [mm] | 5 x 10 | |
| Angle groove [°] | V / 35 | |
| Angle undercut groove [°] | 97 | |
| Car travel [m] | | |
| Ropes weight [Kg] | | |
| Counterweight [Kg] | | |
| Counterweight [%] | | |
| Comp. chains weight [Kg] | | |
| Comp. chains weight [%] | | |
| Out of balance load [Kg] | | |
| Static load [kg] | | |
| Shaft efficiency [%] | | 80 |
| Machine | Above | |
| Divertors on bearings nr | | |
| Divertors on bushing nr | | |
| Minimum alfa angle [°] | | |
| Regulation | 4/00VVVF | |
| Tropicalization | NO | |
| Voltage [V] | 380 | |
| Ropes tensile strength [kg] | | |
| | | |
| Type of ropes | Fiber core | |
| | | |
| **Material not included in price** | | |
| Flat / High frame | | |
| Distance between ropes [mm] | 0 | |
| Vibration dampers | NO | |
| Divertors Ø [mm] | | |
| Divertor protection | | |
| Extended shaft | NO | |
| Centre gear-sheave [mm] | | |
| Centre gear-bearing [mm] | | |
| Static load [Kg] | | |
| | | |

| GEAR / MOTOR | | Price-List € |
|---|---|---|
| **GEAR** | LEO | |
| Quantity n° | 1 | |
| Traction sheave position | to be defined | |
| Ratio | 2/71 | |
| Traction sheave diameter [mm] | 600 | |
| Ropes n° x diameter [mm] | 5 x 10 | |
| Angle groove [°] | V / 35 | |
| Angle undercut groove [°] | 97 | |
| Pitch of grooves [mm] | 17 | |
| Drum Brake voltage DC [V] | 220 | |
| Flywheel | 350-28P | |
| MAX. static load [kg] | 3000 | |
| MAX. out of balance load [kg] | 428 | |
| Traction sheave speed [m/s] | 1,06 | |
| **MOTOR** | SASSI | |
| Frame size | 240118A | |
| Poles / Regulation | 4/00VVVF | |
| Power [kW syncr.] | 7,30 | |
| Voltage [V] | 380 | |
| Rated frequency [Hz] | 50 | |
| Rated current [A] | 17,40 | |
| Acceleration current [A] | 34,80 | |
| Thermistors | 3 | |
| Sts./h. - ED% | 240 40 | |
| Power [kW asyncr.] | 7,30 | |
| Adjusting frequency [Hz/RPM] | 49,91 / 1.497 | |
| Full load current [A] | | |
| **ACCESSORIES** | **Q.ty** | |
| Ropes protection | 1 | |
| Packing | 1 | |

| | Net € | Price-List € |
|---|---|---|
| **Unit price** | | |
| **Total price** | | |

**Payment**
**Goods delivered**
**Packing**

**Offer valid through**

**Delivery time**

ALBERTO SASSI S.p.A. (Gruppo SASSI HOLDING)
Via Guido Rossa,1 - 40056 CRESPELLANO (BO) Italia
Tel. +39 051 672 0202 Fax +39 051 672 0244
http://www.sassi.it E-mail: sassi@sassi.it

Capitale sociale € 2.600.000 i.v.
R.E.A. BO n.405277 - iscr. Reg. Imp. BO
cod. fisc. e partita IVA 01994221206
identificativo CEE IT 01994221206