

Elevator calculation acc. EN81-20/50

Elevator data

Nominal load	Q	kg	630	
Car weight	F	kg	750	(701 - 1057kg)
Counterweight	G	kg	1065	(50%)
Travelling speed	v	(V_3=)	m/s	1,00
Travel distance	H	m	30,0	
Suspension / (roping)	is			2 : 1
Machine at the top, above				
Shaft efficiency	etaS	%	82	
Number of pulleys	(ball bearing)		3	
Type of rope	WOLF F 819 S-FE			
Number of ropes	z		5	
Rope diameter	ds	mm	8	
Rope weight	s	kg	32	(0,215 kg/m)
Compensation rope weight	su	kg	0	
Car cable weight	HK	kg	15	
Rope span weight	R	kg	0	
Min. rope breaking load	B	N	30500	
Traction sheave diameter	Dtr	mm	320	
Sheave width		mm	110	(number of grooves

6)

Groove distance		mm	17,0	Standard
Angle of wrap minimum	min.	deg	180	
Undercutangle		deg	95	
Undercutwidth	b	mm	5,90	
Groove angle		deg	30	

Sheave profile: circular undercut groove

Traction, rope pressure, rope safety

Traction empty, on top, accelerating (1,18)
 1,7387 <= 1,8399
 Traction 150% nominal load, below, not moving
 1,6521 <= 1,8399
 Rope pressure k < permissible rope pressure
 6,14 < 9,00 N/mm²

Conditions according to EN81-1 or -20:
 Load 125% 1,5042 <= 1,8582 (1)
 Emergency stop 1,6396 <= 1,6759 (4)
 with deceleration [m/s²] 0,500
 Blocked car 14,643 > 3,4528 (4)

Real safety factor > Minimum safety factor for ropes
 21,52 > 12
 Rope safety factor according to EN81-1 or -20:
 NEQUIV = 08,7 NEQUIVT = 06,7 NEQUIVP = 02,0
 Pulleys >= 320 mm, pulleys NPR = 0 NPS = 2
 Rope safety nue = 21,5 > 17,8 (minSF)

Rope certification EN81

Traction conditions are fulfilled.

Rope safety conditions are fulfilled.

ZAlift - 20170315 - Machine dimensioning ZA-145528

Mechanical drive data

Machine manufactured by Ziehl-Abegg

Machine type SM 200.20C Gearless synchronous

Machine version ZAtop *

Traction sheave mm 320 /110/17,0/6x8/U95

Load output torque Nm 361 (max. 396)

Real statical axle load kg 1262 (max. 2440)

Brake data

brake Mayr ROBA-twinstop 350, 2x410 Nm, EU-BD 845 (ABV845 + ESV845)

Dual circuit disk brake, DC supply necessary

(298 Nm, 0,54 m/s², 1 m, 6281 J, 164 W)

207 V brake, with hand release, microswitch

Machine load data in the installation

Typical motor operating power kW 2,8

Typ. operating current 14,8 A, Start. Current 23,0 A at acceleration 0,60 m/s²

Start. Current 24,4 A at acceleration 0.7 m/s²

Average power losses 0,66 kW = 2393,07 kJ/h

Output speed rpm 119

Load torque Nm 361,1 (eff. 226,6)

Inertia of installation kgm² 16,47

240 Starts per hour, 40 % required duty cycle at elevator operation

Max. static load pulleys 10449 N, pulley speed 1,00 m/s

Selected ZIEHL-ABEGG motor

Motor type SM200.20C-20 - gearless

	Nameplate data	(Operating
data)		
Rated voltage	V 360	
Rated frequency	Hz 20	(19,9)
Rated torque	Nm 330	(361,1)
Rated speed	rpm 120	(119,4)
Rated output power	kW 4,1	(4,5)
Rated current	A 12,8	(14,8)
Maximum torque	Nm 570	(570)
Current at maximum torque	A 28,5	(28,5)
Inertia of motor	kgm ² 0,160	
Possible acceleration	m/s ² 1,00	
(MKmax=280,0 Nm)		

Without cooling (83)

Dimension sheet A-M-6716, Motor construction type IMB3

Motor with encoder ECN 1313-2048Endat

Selected frequency inverter

Inverter ZAdyn 4CS017, Rated inverter current 17 A
mains current 11,7 A, 400 V, 7,7 kW, Max. 1,00 m/s²
Radio interference filter, integrated ; Line reactor, integrated
Brake resistance separate BR17-3 (or Recuperation: ZArec4C 013)